



RICHWOOD REDI-LAGG

Luff Industries provides a variety high quality lagging options for its customers to choose from, including Richwood Redi-Lagg.

Richwood Redi-Lagg will reduce maintenance costs by providing:

- Improved traction
- Longer pulley life
- Abrasion resistance



Richwood Redi-Lagg - Number of 72" pads required

Pulley Diameter	Pulley Face Width																			
	12	14	16	18	20	22	24	26	30	32	36	38	40	44	46	51	54	60	66	72
10.5	1	1	2	2	2	2	2	2	3	3	3	3	3	4	4	4	4	5	5	5
12.5	1	2	2	2	2	2	2	3	3	3	3	4	4	4	4	5	5	5	6	6
14	2	2	2	2	2	3	3	3	3	4	4	4	4	5	5	5	6	6	7	7
16	2	2	2	2	3	3	3	3	4	4	4	5	5	5	6	6	6	7	8	8
18	2	2	2	3	3	3	3	4	4	4	5	5	5	6	6	7	7	8	9	9
20	2	2	3	3	3	4	4	4	5	5	5	6	6	7	7	8	8	9	10	10
24	2	3	3	3	4	4	4	5	5	6	6	7	7	8	8	9	9	10	11	12
30	3	3	4	4	5	5	5	6	7	7	8	8	9	10	10	11	12	13	14	15
36	3	4	4	5	5	6	6	7	8	8	9	10	10	12	12	13	14	15	17	18
42	4	5	5	6	6	7	7	8	9	10	11	12	12	13	14	15	16	18	20	21
48	4	5	6	6	7	8	8	9	10	11	12	13	14	15	16	17	18	20	22	24
54	5	6	6	7	8	9	9	10	12	12	14	15	15	17	18	20	21	23	25	27
60	5	6	7	8	9	10	10	11	13	14	15	16	17	19	20	22	23	25	28	30
72	6	7	8	9	10	11	12	13	15	16	18	19	20	22	23	26	27	30	33	36

- Redi-Lagg is available in rubber and ceramic weld-on lagging.
- Available in lengths up to 72" long and in 1/2" and 3/4" thicknesses.
- Redi-Lagg can tackle almost any application with standard SBR, as well as anti-static, oil resistant and fire resistant rubber blends available.



Luff Industries Ltd.
235010 Wrangler Road
Rocky View, (Calgary) Alberta, T1X 0K3

TF: 1.888.349.LUFF (5833)
P: 403.279.3555
F: 403.279.5709



Conveying Performance

info@luffindustries.com
www.luffindustries.com